

PVC İZOLELİ, ESNEK, YASSI KABLolar

PVC insulated, flexible, flat cables

HISAR KABLO TS IEC 60227 7 1 f 450/750 V

TS IEC 60227-6
ICS.29.060.20

KULLANIM YERLERİ / APPLICATION

Mekanik zorlamaların az olduğu nemli ve ev gereçlerinde bağlantı kablosu olarak kullanılır.

It's used as connection cables, in dry and humid places that there are not much mechanical compulsion which are generally used in household equipments.

TEKNİK ÖZELLİKLERİ/ SPECIFICATIONS



Bükülgen bakır tel
Flex copper
(Class5)



Max. işletme sıcaklığı
Max. operating temperature



Max. kısa devre sıcaklığı
Max. short circuit temperature



Test gerilimi (A.C. 2,5 kV)
Test voltage (A.C. 2,5 kV)



Serim sıcaklığı (Min. 5°C)
Installation temperature (Min. 5°C)

Cu/PVC/PVC

Anma kesiti Nominal cross (mm ²)	Dış çap (Yaklaşık) Outside diameter (mm)	Net ağırlık Net weight (kg/km)	İletken D.A. direnci Conductor D.C. resistance (20°C ohm/km)	Akım taşıma kapasitesi Current carrying capacity in
				Havada (20°C A) Air
H05VVH6-F / 60227 IEC 7 1 f (450/750 V)				
4x0,75	4,2 x 12,6	94,5	26	6
4x1	4,3 x 13,0	105	19,5	10
4x1,5	4,9 x 14,6	139	13,3	20
4x2,5	5,6 x 18,0	205	7,98	27
4x4	6,5 x 20,0	284	4,95	34
4x6	7,1 x 22,4	375	3,30	48
4x10	8,9 x 28,0	606	1,91	66
4x16	10,3 x 33,2	883	1,21	89
4x25	12,2 x 40,0	1.303	0,780	118
4x35*	13,3 x 44,0	1.716	0,554	145
4x50*	15,9 x 53,2	2.455	0,386	176
4x70*	17,6 x 60,0	3.250	0,272	224
4x95*	19,8 x 67,6	4.334	0,206	271
3x16+10	10,3 x 32,0	829	89	1,21 / 1,91
3x25+16	12,2 x 38,3	1.219	118	0,780 / 1,21

(*) Özel kesitlerdir / Special sections