

PVC İZOLELİ, ESNEK, YASSI KABLolar

PVC insulated, flexible, flat cables

HISAR KABLO TS IEC 60227 7 1 f 450/750 V

TS IEC 60227-6
ICS.29.060.20

KULLANIM YERLERİ / APPLICATION

Mekanik zorlamaların az olduğu nemli ve ev gereçlerinde bağlantı kablosu olarak kullanılır.

It's used as connection cables, in dry and humid places that there are not much mechanical compulsion which are generally used in household equipments.

TEKNİK ÖZELLİKLERİ/ SPECIFICATIONS



Bükülgen bakır tel
Flex copper
(Class5)



Max. işletme sıcaklığı
Max. operating temperature



Max. kısa devre sıcaklığı
Max. short circuit temperature



Test gerilimi (A.C. 2,5 kV)
Test voltage (A.C. 2,5 kV)



Serim sıcaklığı (Min. 5°C)
Installation temperature (Min. 5°C)

Cu/PVC/PVC

Anma kesiti Nominal cross (mm ²)	Dış çap (Yaklaşık) Outside diameter (mm)	Net ağırlık Net weight (kg/km)	İletken D.A. direnci Conductor D.C. resistance (20°C ohm/km)	Akım taşıma kapasitesi Current carrying capacity in Havada (20°C A) Air
5x0,75	4,2 x 15,0	115	26	6
5x1	4,3 x 15,5	128	19,5	10
5x1,5	4,9 x 17,5	170	13,3	20
5x2,5	5,6 x 21,6	252	7,98	27
5x4	6,5 x 24,1	349	4,95	34
5x6	7,1 x 27,1	463	3,30	48
5x10	8,9 x 34,1	752	1,91	66
5x16	10,3 x 40,5	1.097	1,21	89
5x25	12,2 x 49,0	1.622	0,780	118
5x35*	13,3 x 53,9	2.138	0,554	145
5x50*	15,9 x 65,3	3.060	0,386	176
5x70*	17,6 x 73,8	4.056	0,272	224
5x95*	19,8 x 83,2	5.410	0,206	271

(* Özel kesitlerdir / Special sections